

VM1500 - Data Sheet



SPECIFICATION



MODEL: VM1500		12V	24V	48V
OUTPUT	Rated Power	1500W		
	Maximum Output Power	3000W SURGE POWER		
	AC Voltage	200~240VAC (Standard) or 100~120VAC (Special Order)		
	Frequency	50Hz±0.1% (Standard) or 60Hz±0.1% (Special Order)		
	Waveform	Modified sine wave output (THD<3%) at rated input voltage		
	Socket Types	UK		
	Led Indicator Light	Inverter and Fault		
INPUT	Bat.Voltage	12V	24V	48V
	Voltage Range	10V-15V	20V-30V	40V-60V
	DC Current	150A	75A	37.5A
	No Load Consumption	<0.6A	<0.3A	<0.15A
	Efficiency	>88%		
	Battery Types	Open & sealed lead acid battery		
BATTERY INPUT PROTECTION	Fuses	35A*6	20A*6	10A*6
	Low Voltage Alarm	10.5V± 0.5V	21V±1V	42V±2V
	Low Voltage Shut down	10V± 0.5V	20V±1V	40V±2V
	Over Voltage Shut down	1800W over 10 seconds		
	Reverse Polarity	By fuse open		
OUTPUT PROTECTION	Over Temperature	Shut Off Output Automatically, Temperature >75°		
	Output Short	Protection type: Shut down o/p voltage, re-power on to recover		
	Over Load	Protection type: Shut down o/p voltage, re-power on to recover		
ENVIRONMENT	Working Temp.	-10°C ~ +50°		
	Working Humidity	20% ~ 90% RH Non-Condensing		
	Storage Temp.	-30°C ~ +70°C		
SAFETY	CE EMC	Compliance to EN61000-3-2,3; EN55022; EN55024		
	CE LVD	Compliance to EN62040-1:2008		
	RoHS	Compliance to 2011/65/EU		
PACKING	Inner Box	405*286*168 mm, 5kg		
	Carton	430*305*355 mm, 11kg		
	Package	2pcs /Carton		
ACCESSORIES	Battery Cable	2x Positive & 2x Negative Battery Cables		
	User Manual	1x English Manual		
	Fuse	6x Replaceable fuses		

Guaranteed Performance

1 Years Manufacturers Warranty

Sunshine Solar Limited
Unit 29, Ashwellthorpe Industrial Estate Ashwellthorpe
Norwich Norfolk NR16 1ER

Tel: +44 (0)1508 488188 - Fax: +44 (0)1508 488288

www.sunshinesolar.co.uk - sales@sunshinesolar.co.uk