

VMS150 - Data Sheet



SPECIFICATION

MODEL: VMS150		12V	24V	
OUTPUT	Rated Power	150W		
	Maximum Output Power	300W SURGE POWER		
	AC Voltage	200~240VAC (Standard) 100~120VAC (Special Order)		
	Frequency	50Hz±0.1% (Standard) 60Hz±0.1% (Special Order)		
	Waveform	Modified sine wave output (THD<3%) at rated input voltage		
	Socket Types	UK		
	Led Indicator Light	Inverter and Fault		
INPUT	Bat.Voltage	12V	24V	
	Voltage Range	10V-15V	20V-30V	
	DC Current	15A	7.5A	
	No Load Consumption	<0.3A	<0.15A	
	Efficiency	>88%		
	Battery Types	Open & sealed lead acid battery		
BATTERY INPUT PROTECTION	Fuses	35A*1	20A*1	
	Low Voltage Alarm	10.5V± 0.5V	21V±1V	
	Low Voltage Shut down	10V± 0.5V	20V±1V	
	Over Voltage Shut down	15V±0.5V	30V±1V	
	Reverse Polarity	By fuse open		
OUTPUT PROTECTION	Over Temperature	Shut Off Output Automatically, Temperature >75°		
	Output Short	Protection type: Shut down o/p voltage, re-power on to recover		
	Over Load	Protection type: Shut down o/p voltage, re-power on to recover		
ENVIRONMENT	Working Temp.	-10°C ~ +50°		
	Working Humidity	20% ~ 90% RH Non-Condensing		
	Storage Temp.	-30°C ~ +70°		
SAFETY	CE EMC	Compliance to EN61000-3-2,3; EN55022; EN55024		
	CE LVD	Compliance to EN62040-1:2008		
	RoHS	Compliance to 2011/65/EU		
PACKING	Inner Box	205*175*75 mm, 1kg		
	Carton	435*370*370 mm, 16.5kg		
	Package	16pcs /Carton		
ACCESSORIES	Battery Cable	1x Positive & 1x Negative Battery Cables		
	User Manual	1x English Manual		
	Fuse	1x Replaceable fuse		

Guaranteed Performance

1 Years Manufacturers Warranty

Sunshine Solar Limited
Unit 29, Ashwellthorpe Industrial Estate Ashwellthorpe
Norwich Norfolk NR16 1ER

Tel: +44 (0)1508 488188 - Fax: +44 (0)1508 488288

www.sunshinesolar.co.uk - sales@sunshinesolar.co.uk