

## SSP160P

### 160W Rigid Solar Panel



|                                     |                       |
|-------------------------------------|-----------------------|
| Maximum Power (Pmax)                | 160W $\pm$ 5%         |
| Maximum Power Current (Ipm)         | 8.84A                 |
| Maximum Power Voltage (Vpm)         | 18.10V                |
| Short Circuit Current (Isc)         | 9.15A                 |
| Open Circuit Voltage (Voc)          | 22.4V                 |
| Nominal Operating Cell Temp. (NOCT) | -40 to 85°C           |
| Cell Efficiency %                   | 18.43                 |
| Size                                | 1470mm x 664mm x 35mm |
| Weight                              | 10.3kg                |

#### Features

- Aluminium Frame
- Toughened Glass
- 4mm Single Core Cable fitted with type MC4 Connectors (length 900mm)
- High Performance Crystalline Cells

*5 Years Manufacturers Warranty*

*10 Years Warranty 90% Power Output*

*20 Years Warranty 80% Power Output*

Sunshine Solar Limited  
Unit 30, Ashwellthorpe Industrial Estate Ashwellthorpe  
Norwich Norfolk NR16 1ER

Tel: +44 (0)1508 488188

[www.sunshinesolar.co.uk](http://www.sunshinesolar.co.uk) - [support@sunshinesolar.co.uk](mailto:support@sunshinesolar.co.uk)

